



750 °C Series



Platinum sensor with wires



For very high temperatures



Benefits & characteristics




- Excellent long-term stability
- Low self-heating
- Fast response time



- Vibration and temperature shock resistant
- Simple interchangeability
- Customer-specific sensor available upon request



Illustration ¹⁾



¹⁾ for actual size see dimensions in order information

H = Substrate Hight

H2 =Hight

W = Width

L = Length

L_w = Wire length

Dimension tolerances:

W ±0.2 mm, L ±0.2 mm, H ±0.1 mm, H2 ±0.3 mm,

L_w (up to 30 mm) ±1 mm



Technical Data

Operating temperature range:	-200 °C to +750 °C	
Nominal resistance:*	100 Ω at 0 °C	
	500 Ω at 0 °C	
	1000 Ω at 0 °C	
Characteristics curve:*	3850 ppm/K	
Long-term stability:	< 0.04 % at 1000 h at maximal operating temperature	
Tolerance class: * (dependent on temperature range)	iST reference	
	IEC 60751 F0.15	A
	IEC 60751 F0.3	B
	IEC 60751 F0.6	C
	IEC 60751 F0.1	Y
Connection:*	Pt-wire, Ø 0.2 mm (solderable, weldable, crimpable, brazeable)	
Recommended applied current: ¹⁾	1 mA at 100 Ω	
¹⁾ Self-heating must be considered	0.5 mA at 500 Ω	
	0.3 mA at 1000 Ω	
Other alternatives:*	Grouped and paired	
	Substrate thickness	

* [Customer-specific alternatives available](#)



Order Information

Nominal Resistance at 0 °C	Size	Dimensions (L x W x H / H2 in mm) L ±0.2, W ±0.2, H ±0.1, H2 ±0.3 mm	Class*	Order code	Product name (secondary reference)	Wire length in mm	Special
7W (Pt-wire, Ø 0.2 mm)							
1000 Ω	216	2.5 x 1.6 x 0.65 / 1.1	F0.1 (class Y)	On request	P1K0.216.7W.Y.010	10	
1000 Ω	216	2.5 x 1.6 x 0.65 / 1.1	F0.15 (class A)	On request	P1K0.216.7W.A.010	10	
1000 Ω	216	2.5 x 1.6 x 0.65 / 1.1	F0.3 (class B)	104051	P1K0.216.7W.B.010	10	
100 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.1 (class Y)	On request	P0K1.516.7W.Y.007	7	
100 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.15 (class A)	100425	P0K1.516.7W.A.007	7	
100 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.3 (class B)	100424	P0K1.516.7W.B.007	7	
500 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.1 (class Y)	On request	P0K5.516.7W.Y.007	7	
500 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.15 (class A)	On request	P0K5.516.7W.A.007	7	
500 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.3 (class B)	On request	P0K5.516.7W.B.007	7	
1000 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.1 (class Y)	100726	P1K0.516.7W.Y.010	10	
1000 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.15 (class A)	100572	P1K0.516.7W.A.010	10	
1000 Ω	516	5.0 x 1.6 x 0.65 / 1.1	F0.3 (class B)	100571	P1K0.516.7W.B.010	10	
1000 Ω	520	5.0 x 2.2 x 0.65 / 1.1	F0.1 (class Y)	On request	P1K0.520.7W.Y.010	10	
1000 Ω	520	5.0 x 2.2 x 0.65 / 1.1	F0.15 (class A)	100512	P1K0.520.7W.A.010	10	
1000 Ω	520	5.0 x 2.2 x 0.65 / 1.1	F0.3 (class B)	100288	P1K0.520.7W.B.010	10	
100 Ω	102	10.0 x 2.0 x 0.65 / 1.1	F0.1 (class Y)	On request	P0K1.102.7W.Y.010	10	
100 Ω	102	10.0 x 2.0 x 0.65 / 1.1	F0.15 (class A)	150013	P0K1.102.7W.A.010	10	
100 Ω	102	10.0 x 2.0 x 0.65 / 1.1	F0.3 (class B)	100203	P0K1.102.7W.B.010	10	
1000 Ω	102	10.0 x 2.0 x 0.65 / 1.1	F0.1 (class Y)	On request	P1K0.102.7W.Y.010	10	
1000 Ω	102	10.0 x 2.0 x 0.65 / 1.1	F0.15 (class A)	On request	P1K0.102.7W.A.010	10	
1000 Ω	102	10.0 x 2.0 x 0.65 / 1.1	F0.3 (class B)	On request	P1K0.102.7W.B.010	10	

Additional Documents

Application Note

Document name: APT_E



Order Information

Platinum Sensor - Secondary reference



Material

P = Platinum

TCR

= Pt 3850 ppm/K G = Pt 3911 ppm/K
U = Pt 3750 ppm/K W = Pt 3850 ppm/K (extended operating temperature range in class A)

Resistance in Ω at 0°C

Size in mm

Operating temperature range

1 = -50 °C to + 150 °C	6 = -200°C to + 600 °C
2 = -50 °C to + 200 °C	7 = -200 °C to + 750 °C
3 = -200 °C to + 300 °C	8 = -200 °C to + 850 °C
4 = -200 °C to + 400 °C	10 = -70 °C to + 1000 °C

Connections

S = SIL	FK = Flat wire customer specific
I = Insulated wire	SW = Perpendicular wire
K = Extended wire	L = Insulated stranded wire
W = Wire	E = Enameled Cu-wire
FW = Flat wire	SE = Perpendicular enameled Cu-wire

Tolerance class

A = IEC 60751 F0.15	K = Customer-specific
B = IEC 60751 F0.3	P = Pair
C = IEC 60751 F0.6	G = Group
Y = IEC 60751 F0.1	

Wire length in mm

Special

T = Substrate thickness 0.25 mm	M = Metallized backside
D = Substrate thickness 0.38 mm	U = Inverted welding
R = Round housing	S = Special
W = Sintered powder	

P OK1. 516. 7 W. A. 010



Innovative Sensor Technology IST AG • Stegrütistrasse 14 • 9642 Ebnat-Kappel • Switzerland

+41 71 992 01 00 • info@ist-ag.com • www.ist-ag.com

Technical specifications are subject to change without prior notice. The information contained in this data sheet has been carefully reviewed and is believed to be accurate; however, no liability is assumed for any errors or omissions. Continuous exposure to extreme operating conditions may impact product lifetime or reliability. The customer is solely responsible for assessing the suitability and fitness of the product for their specific application. This product is not designed, authorized, or warranted for use in life support or safety-critical applications. The customer agrees to hold the supplier harmless from any claims, damages, or liabilities arising from such use. No explicit or implied warranties, including but not limited to warranties of merchantability or fitness for a particular purpose, are provided. The material provided herein may not be reproduced, adapted, merged, translated, stored, or utilized in any form without prior written consent from the copyright holder. No transfer of any intellectual property rights is granted or implied. All rights reserved.